

Unit : mm

品號 Ring No.	止輪尺寸 Ring Dimension								d ₅ Clearance Dia.	適用軸尺寸 Shaft Dimension (Reference Only)					
	d ₃		d ₄	t		h	do Hole Dia.	公差 Tol.		d ₁ Shaft Dia.	d ₂		m		n 最小 min.
基本尺寸 Free Dia.	公差 Tol.	基本尺寸 Thickness		公差 Tol.	公差 Tol.				公差 Tol.		基本尺寸 Groove Dia.	公差 Tol.	基本尺寸 Width	公差 Tol.	
IS-6	5.6		8	0.5		1.2	2.2		8.9	6	5.7	-0.04	0.6		
7	6.5	+0.1	9.3	0.6		1.4	2.4		10.3	7	6.7	+0	0.7	+0.1	
8	7.4	-0.2	10.6	0.7		1.6	3.0	±0.2	11.7	8	7.6	-0.06	0.8	-0	
9	8.4		12	0.8		1.8	3.4		13.1	9	8.6		0.95		
10	9.3	±0.15	13.3		±0.04	2.0			14.5	10	9.6	-0.09			
11	10.2		14.4			2.1			16	11	10.5				
12	11.1		15.5			2.2			17.2	12	11.5				
13	12		16.6			2.3			18.4	13	12.4	+0	1.15		
14	12.9		17.5	1.0		2.3	1.2		19.4	14	13.4	-0.11			
15	13.8	±0.18	18.6			2.4		±0.3	20.6	15	14.3			1.5	
16	14.7		19.7			2.5			21.8	16	15.2				
17	15.7		20.9			2.6			23	17	16.2				
18	16.5		21.9			2.7			24.2	18	17.0			±0.14	
19	17.5		23.1			2.8			25.4	19	18.0				
20	18.5		24.3		2.9			27	20	19.0					
21	19.5		25.5		3.0			28	21	20.0					
22	20.5		26.5	1.2	3.0	1.5		29	22	21.0		1.35			
24	22.2	±0.2	28.6		3.2		±0.05	31.5	24	22.9	+0				
25	23.2		29.8		3.3			33	25	23.9	-0.21				
26	24.2		31		3.4			34	26	24.9					
28	25.9		33.1		3.6		±0.4	36.5	28	26.6					
30	27.9		35.3	1.5	3.7	1.8		38.5	30	28.6		1.65			
35	32.2		40.6		4.2			45	35	33.0					
36	33.2	±0.25	41.6		4.2			46	36	34	+0				
38	35.2		44.0	1.75	4.4	2.0		48	38	36.0	-0.25	1.9			
42	38.5	±0.4	48.1		4.8		±0.06	54	42	39.5			2.0		
60	55.8	±0.45	68.4	2.0	6.3	2.5		75	60	57.0	+0/-0.3	2.2			


*未顯示於表格之規格歡迎來電洽詢

*Other sizes may be available upon request

Copyright (c) 2020 HJ Spring Co., Ltd. All Rights Reserved



- ◎ 小尺寸規格 Alternative Design
IS-9以下為無孔設計
Special Lug for ring sizes IS-6 thru IS-9



- ◎ 規格標準 Standard Reference
日本工業規格 JIS B 2804

- ◎ 材質&硬度(參考) Material & Hardness Ranges (Rockwell scale)
彈簧鋼 · 硬度HRC 40-50 Carbon Spring Steel SAE1050~SAE1090, HRC40~HRC50

- ◎ 表面 Finish
染黑 Black Oxide

- ◎ 包裝方式 Packaging
散裝 Bulk