



Unit : mm

品 號 Ring No.	止輪尺寸 Ring Dimension						適用軸尺寸 Shaft Dimension (Reference Only)					
	d		D Clearance Dia.	b	t		d <sub>1</sub> Shaft Dia.	d <sub>2</sub>		m		n 最小 Min.
基本尺寸 Free Dia.	公差 Tol.	基本尺寸 Thickness			公差 Tol.	基本尺寸 Groove Dia.		公差 Tol.	基本尺寸 Width	公差 Tol.		
CT- 12	2.59	+0.05	4.17	0.79	0.4	±0.03	3.2	2.69	±0.04	0.48	+0.04	0.5
18	4.09	-0.1	6.19	1.05	0.4		4.8	4.19		0.48	-0	0.6
21	4.75	+0.07 -0.13	6.99	1.12	0.6	±0.04	5.6	4.9	±0.05	0.7	+0.06 -0	0.7
25	5.36		7.90	1.27	0.6		6.4	5.59		0.7		0.8
31	6.86		9.56	1.35	0.6		7.9	7.01		0.7		0.9
37	8.33		11.37	1.52	0.6		9.5	8.51		0.7		1.0
40	9.12		12.32	1.60	0.6		10.3	9.25		0.7		1.1
43	9.8	13.10	1.65	0.6	11.1	9.98	0.7	1.1				
46	10.54	±0.15	14.00	1.73	0.6	11.9	10.69	±0.07	0.7	+0.08 -0	1.2	
50	11.2		14.76	1.78	0.9	12.7	11.43		1		1.3	
56	12.62		16.56	1.98	0.9	14.3	12.88		1		1.4	
81	18.31	±0.18	23.23	2.46	1.4	±0.05	20.6	18.59	1.5	-0	2.3	

\*未顯示於表格之規格歡迎來電洽詢

Copyright (c) 2020 HJ Spring Co., Ltd. All Rights Reserved

\*Other sizes may be available upon request

◎ 規格標準 Standard Reference

WALDES TRUARC, series 5103  
Arcon, series N1800

◎ 材質&硬度(參考) Material & Hardness Ranges (Rockwell scale)

彈簧鋼 · 硬度HRC 44-53 Carbon Spring Steel SAE1050~SAE1090, HRC44~HRC53  
不鏽鋼SUS420 · 硬度HRC 36-44 Stainless Steel Type 420, HRC36~HRC44 (Not all sizes in Stainless in stock)

◎ 表面 Finish

原色 Plain  
染黑 Black Oxide  
鍍鎳 Nickel Plating

◎ 包裝方式 Packaging

散裝 Bulk  
條裝 Stacked  
(Not all sizes in Stacked in stock)